

MARVELL® 88SS1323 SSD Controller

PCIe Gen 4x2, 4-Channel DRAMIess High-Performance SSD Controller with NVMe 1.3c interface

PRODUCT OVERVIEW

The Marvell® 88SS1323 enables high performance and high capacity SSDs for use in small form factor applications such as cloud data center compute server storage, enterprise boot drives, PC client storage and gaming storage as well as emerging industrial and edge device applications.

Leveraging a tri-core Arm[®] Cortex[®] R5 architecture that supports DRAMless operations, the product is ideally suited for m.2 2230, 2242, 2280 SSDs in single and double-sided form factors. It also supports BGA 1113 and BGA1620 FF SSDs. The Marvell 88SS1323 controller supports PCIe Gen 4 and four ONFI and TOGGLE NAND channels operating at up to 1200MT/s, that enable high capacity, high throughput and low latency storage over a wide range of use cases.

The common hardware and firmware controller architecture in 12nm process technology provides the best-in-class electrical and thermal characteristics as well as ultra-low power consumption.

The 88SS1323 leverages the 4th generation of the Marvell NANDEdge™ LDPC engine for extracting the highest level of error correction capability and low-latency read retries and endurance to support the next generation TLC and QLC memories.

The SSD controller also supports TCG standards including an AES engine and OTP storage for secure drive configuration.



BLOCK DIAGRAM

Marvell 88SS1323 SSD Controller

KEY FEATURES AND BENEFITS

FEATURES	BENEFITS
Processor	• Tri-Cortex R5 CPUs
Interface	PCIe Gen 4x2 and Gen 3x26G SATA
DDR Controller	• DRAMIess
Flash Controller	 4 Channels @ 1200MT/s Up to 16 CEs (4CH x 4 CE/Channel) Compatible with ONFI 2.2/2.3/3.0/4.0/4.1, JEDEC mode and Toggle 1.0/2.0/3.0/4.0 Hardware RAID 4th generation of Marvell NANDEdge[™] LDPC engine
NVMe	 NVMe Standard Revision 1.3c compliance Supports Host Memory Buffer (HMB) Option
Data Protection & Security	 End-to-end data protection OTP support for secure drive configuration AES encryption hardware
Temperature Support	 OC to 70C (C-temp) -40C to 85C (I-temp) On-Die Temperature Sensor
Performance	 128KB Sequential Read up to 3.5 GB/s 128KB Sequential Write up to 3.0 GB/s 4K Random Read up to 450K IOPS 4K Random Write up to 350K IOPS
Deep Sleep Idle Power	• PS4 (L.1.2): ~1mW
Package	• 8mm x 11mm (234 ball) FC-TFBGA package

TARGET APPLICATIONS

- PC Client
- Gaming
- Industrial
- Data Center
- Enterprise Boot-Drive
 DRAMless SSDs







ABOUT MARVELL: Marvell first revolutionized the digital storage industry by moving information at speeds never thought possible. Today, that same breakthrough innovation remains at the heart of the company's storage, networking and connectivity solutions. With leading intellectual property and deep system-level knowledge, Marvell semiconductor solutions continue to transform the enterprise, cloud, automotive, industrial, and consumer markets. For more information, visit <u>www.marvell.com</u>.

Marvell_88SS1323_PB Revised: 08/19 Copyright © 2019 Marvell. All rights reserved. Marvell and the Marvell logo are registered trademarks of Marvell and/or its affiliates in the U.S. and/or elsewhere. NANDEdge is a trademark of Marvell and/or its affiliates in the U.S. and/or elsewhere. Other names and brands may be claimed as the property of others.